


PRESSURES UP TO 3000 PSI

CYLINDER VALVE OUTLET LEFT HAND MALE



INLET CONNECTION

LEFT HAND


FEMALE NUT & NIPPLE

CONNECTION NO. 555

All dimensions are in inches - for reference only, subject to change.

CYLINDER VALVE OUTLET CAPS

PART NUMBER	DESCRIPTION	L
CAP-555BR-P	BRASS W/ POLY DISC LESS RING & CHAIN	0.54"
CAP-555BR-PR	BRASS W/ POLY DISC	0.54"
CAP-555CH-P	NICKEL PLATED BRASS W/ POLY DISC LESS RING & CHAIN	0.54"
CAP-555CH-PR	NICKEL PLATED BRASS W/ POLY DISC	0.54"




INLETS X 1/4" MALE NATIONAL PIPE THREAD (INCLUDES NUT & NIPPLE)

PART NUMBER	DESCRIPTION	L
INL-555BR-4M-48	BRASS	3.00"
INL-CV555BR-4M	BRASS W/ CHECK VALVE	3.00"
INL-555CH-4M-48	NICKEL PLATED BRASS	3.00"
INL-555CH-4M-48R	NICKEL PLATED BRASS W/ FILTER	3.00"
INL-CV555CH-4M	NICKEL PLATED BRASS W/ CHECK VALVE	3.00"
INL-555SS-4M-36	STAINLESS STEEL	2.25"
INL-555SS-4M-48	STAINLESS STEEL	3.00"
INL-555SS-4M-70R	STAINLESS STEEL W FILTER	4.375"
INL-CV555SS-4M	STAINLESS STEEL W/ CHECK VALVE	2.625"

STAINLESS STEEL 303 NUT, 316L NIPPLE

BRASS OR NICKEL PLATED BRASS NUT & NIPPLE






INLETS X 1/4 MALE FACE SEAL (INCLUDES 303 SS NUT & 316L SS NIPPLE)


PART NUMBER	DESCRIPTION	L
INL-555SS-4MFS-36	STAINLESS STEEL 12 Ra	2.25"
INL-555SS-4MFS-P	STAINLESS STEEL 9 Ra EP	2.25"

Available with Check Valve upon request $\mathsf{EP} = \mathsf{Electropolished\ ID}$



INLETS X ORBITAL TUBE WELD STUB (INCLUDES SILVER PLATED 303 SS NUT & 316L SS NIPPLE)

PART NUMBER	DESCRIPTION	L	T
INL-555SS-4TS-36F	STAINLESS STEEL 12 Ra*	2.25"	1/4"0D X .035" WALL
INL-555SS-4TS-P	STAINLESS STEEL 9 Ra EP*	2.25"	1/4"0D X .035" WALL
INL-CV555SS-4TS	STAINLESS STEEL W/ CHECK VALVE	2.21"	1/4"0D X .035" WALL
INL-555SS-6TS	STAINLESS STEEL 12 Ra	2.25"	3/8"0D X .035" WALL
INL-555SS-6TS-P	STAINLESS STEEL 9 Ra EP	2.25"	3/8"0D X .035" WALL
INL-555SS-8TS-36F	STAINLESS STEEL 12 Ra	2.25"	1/2"0D X .049" WALL
INL-555SS-8TS-P	STAINLESS STEEL 9 Ra EP	2.25"	1/2"0D X .049" WALL



*PTH-7 Pigtail Handle available

EP = Electropolished ID



GasFlo Products Inc. CGA Compressed Gas Service Cylinder Connections are Manufactured to CGA V-1 Standards

Additional materials and configurations available on request. Minimum order quantities may be required.





PRESSURES UP TO 3000 PSI

COMPLETE PIGTAIL CONNECTION X ORBITAL TUBE WELD STUB (INCLUDES 303 SS NUT, 316L SS NIPPLE, & 303 SS BLANK PLUG)

PART NUMBER	DESCRIPTION	L	Т
PT-555SS-4TS-P	STAINLESS STEEL 9 Ra EP*	2.25"	1/4" OD x .035" WALL
PT-555SS-6TS-P	STAINLESS STEEL 9 Ra EP	2.25"	3/8" OD x .035" WALL
PT-555SS-8TS-P	STAINLESS STEEL 9 Ra EP	2.25"	1/2" OD x .049" WALL

Blank plug available with ring & chain on request *PTH

*PTH-7 Pigtail Handle available EP = Electropolished ID


COMPLETE PIGTAIL CONNECTION X 1/4 MALE FACE SEAL (INCLUDES 303 SS NUT, 316L NIPPLE, & 303 SS BLANK PLUG)

PART NUMBER	DESCRIPTION	L
PT-555SS-4MFS-P	STAINLESS STEEL 9 Ra EP	2.25"

Blank plug available with ring & chain on request


 $\mathsf{EP} = \mathsf{Electropolished} \; \mathsf{ID}$

INLET OPTIONS & ACCESSORIES







PTH-7
PIGTAIL HANDLE SIZE
7 FOR USE ON 1/4"
TUBE STUB INLETS
ONLY



VALVE OUTLET ADAPTORS



1/2" MNPT




PART NUMBER	DESCRIPTION	L
AD-555MBR-4FNPT	BRASS 1/4" FNPT	1.31"
AD-555MBR-4MNPT	BRASS 1/4" MNPT	1.80"
AD-555MBR-8MNPT	BRASS 1/2" MNPT	2.00"
AD-555MSS-BL	303 SS BLANK CAP	1.12"
AD-555MSS-4FNPT	316L SS 1/4" FNPT	1.31"
AD-555MSS-4MNPT	316L SS 1/4" MNPT	2.19"
AD-555MSS-8MNPT	316L SS 1/2" MNPT	2.00"
AD-555MSS-4MFS	316L SS 1/4 MALE FACE SEAL	2.14"

Blank cap available with ring & chain on request

3 PIECE ADAPTORS (INCLUDES 303 SS NUT, 316L SS NIPPLE & SS OUTLET ADAPTOR)

PART NUMBER	DESCRIPTION	L
AD-555F718M-SS	STAINLESS STEEL CGA 555 FEMALE X CGA 714 MALE	4.50"
AD-555FBS3F-SS	STAINLESS STEEL CGA 555 FEMALE X BS 3 FEMALE	4.40"
AD-555FD10M-SS	STAINLESS STEEL CGA 555 FEMALE X DIN 10 MALE	3.77"
AD-555FAFNORCF-SS	STAINLESS STEEL CGA 555 FEMALE X AFNOR C FEMALE	3.86"
AD-555FJ22RM-SS	STAINLESS STEEL CGA 555 FEMALE X JIS 22R MALE	3.96"



VALVE, FITTING OR OTHER COMPONENT FUNCTION, PROPER INSTALLATION, MATERIALS COMPATIBILITY, ADEQUATE RATINGS, OPERATION AND MAINTENANCE ARE THE RESPONSIBILTY OF THE SYSTEM DESIGNER AND USER.



PRODUCT FAILURE, IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.



GasFlo Products Inc. CGA Compressed Gas Service Cylinder Connections are Manufactured to CGA V-1 Standards
Additional materials and configurations available on request. Minimum order quantities may be required.