


PRESSURES UP TO 3000 PSI

CYLINDER VALVE OUTLET RIGHT HAND MALE






INLET CONNECTION RIGHT HAND FEMALE NUT & NIPPLE

### **CONNECTION NO. 638**

All dimensions are in inches - for reference only, subject to change.


# **CYLINDER VALVE OUTLET CAPS**

PART NUMBER	DESCRIPTION	L
CAP-GT63SS	STAINLESS STEEL GAS TIGHT L/ GASKET	1.27"
CAP-GT63SS-K	STAINLESS STEEL GAS TIGHT W/ PCTFE GASKET	1.27"
CAP-GT63SS-NI	STAINLESS STEEL GAS TIGHT W/ NICKEL 200 GASKET	1.27"




## **GASKETS**

PART NUMBER	DESCRIPTION	D	Н	W
GSK-DISS-K	VIRGIN PCTFE	.562	.210	.125
GSK-DISS-NI	NICKEL 200	.562	.210	.125
GSK-DISS-AL	ALUMINUM 2024	.562	.210	.125



# INLETS X 1/4" MALE NATIONAL PIPE THREAD (INCLUDES SILVER PLATED 303 SS NUT & 316L SS NIPPLE)


PART NUMBER	DESCRIPTION	L
INL-638SS-4M	STAINLESS STEEL 9 Ra EP	3.00"
INL-638SS-4M-N	STAINLESS STEEL 9 Ra EP W/ NICKEL GASKET	3.00"



 $\mathsf{EP} = \mathsf{Electropolished}\;\mathsf{ID}$ 


## INLETS X 1/4 MALE FACE SEAL (INCLUDES SILVER PLATED 303 SS NUT & 316L SCM SS NIPPLE)

PART NUMBER	DESCRIPTION	L
INL-638SS-4MFS	STAINLESS STEEL 9 Ra EP	3.00"
INL-638SS-4MFS-N	STAINLESS STEEL 9 Ra EP W/ NICKEL GASKET	3.00"
EP = Electropolished ID	SCM = Semiconductor Material (VIM/VAR)	



## INLETS X ORBITAL TUBE WELD STUB (INCLUDES SILVER PLATED 303 SS NUT & 316L SCM SS NIPPLE)

PART NUMBER	DESCRIPTION	L	T
INL-638SS-4TS	STAINLESS STEEL 9 Ra EP	2.50"	1/4"0D X .035" WALL
INL-638SS-4TS-N	STAINLESS STEEL 9 Ra EP W/ NICKEL GASKET	2.50"	1/4"0D X .035" WALL
INL-638SS-6TS	STAINLESS STEEL 9 Ra EP	2.375"	3/8"0D X .035" WALL
INL-638SS-6TS-N	STAINLESS STEEL 9 Ra EP W/ NICKEL GASKET	2.375"	3/8"0D X .035" WALL
INL-638SS-8TS	STAINLESS STEEL 9 Ra EP	2.375"	1/2"0D X .049" WALL
INL-638SS-8TS-N	STAINLESS STEEL 9 Ra EP W/ NICKEL GASKET	2.375"	1/2"0D X .049" WALL




EP = Electropolished ID SCM = Semiconductor Material (VIM/VAR)

#### **ACCESSORIES INLET OPTIONS**

PART NUMBER TORQUE SETTING TW-DISS-NI 35 FT-LB FOR NICKEL & ALUMINUM GASKETS TW-DISS-K 12 FT-LB FOR PCTFE GASKETS










GasFio Products Inc. CGA Ultra High Integrity Service Cylinder Connections are Manufactured to CGA V-1 Standards Additional materials and configurations available on request. Minimum order quantities may be required.








PRESSURES UP TO 3000 PSI

# COMPLETE PIGTAIL CONNECTION X ORBITAL TUBE WELD STUB

(INCLUDES SILVER PLATED 303 SS NUT, 316L SCM SS NIPPLE, 303 SS BLANK PLUG & GASKET)

PART NUMBER	DESCRIPTION	L	Т
PT-638SS-4TS	STAINLESS STEEL 9 Ra EP W/ PCTFE GASKET	2.50"	1/4" OD x .035" WALL
PT-638SS-6TS	STAINLESS STEEL 9 Ra EP W/ PCTFE GASKET	2.375"	3/8" OD x .035" WALL
PT-638SS-8TS	STAINLESS STEEL 9 Ra EP W/ PCTFE GASKET	2.375"	1/2" OD x .049" WALL
PT-638SS-4TS-N	STAINLESS STEEL 9 Ra EP W/ NICKEL GASKET	2.50"	1/4" OD x .035" WALL
PT-638SS-6TS-N	STAINLESS STEEL 9 Ra EP W/ NICKEL GASKET	2.375"	3/8" OD x .035" WALL
PT-638SS-8TS-N	STAINLESS STEEL 9 Ra EP W/ NICKEL GASKET	2.375"	1/2" OD x .049" WALL
ED Floring Palent	ID COM Control of the Male to AMMANAD		



EP = Electropolished ID SCM = Semiconductor Material (VIM/VAR)

# COMPLETE PIGTAIL ADVANCED PERFORMANCE CONNECTION X ORBITAL TUBE WELD STUB


(INCLUDES SILVER PLATED 303 SS AP NUT, 316L SCM SS NIPPLE, 303 SS BLANK PLUG & GASKET)

					— 1.53° — <del></del>	
PART NUMBER	DESCRIPTION	L	T	-		
PT-AP-638SS-4TS-N	STAINLESS STEEL 9 Ra EP W/ NICKEL GASKET	2.50"	1/4" OD x .035" WALL	1.25"		Ĥ
PT-AP-638SS-8TS-N	STAINLESS STEEL 9 Ra EP W/ NICKEL GASKET	2.375"	1/2" OD x .049" WALL			ťĐ
EP = Electropolished ID	SCM = Semiconductor Material (VIM/VAR)			-	— 1 1/8" H	HEX


# **COMPLETE PIGTAIL CONNECTION X 1/4 MALE FACE SEAL**

(INCLUDES SILVER PLATED 303 SS NUT, 316L SCM SS NIPPLE, 303 SS BLANK PLUG, & GASKET)

PART NUMBER	DESCRIPTION	L
PT-638SS-4MFS	STAINLESS STEEL 9 Ra EP W/ PCTFE GASKET	3.00"
PT-638SS-4MFS-N	STAINLESS STEEL 9 Ra EP W/ NICKEL GASKET	3.00"
EP = Electropolished ID	SCM = Semiconductor Material (VIM/VAR)	



## **VALVE OUTLET ADAPTORS**




PART NUMBER	DESCRIPTION	L
AD-63SS-BL	316L SS BLANK PLUG*	1.53"
AD-638MSS-4FNPT	316L SS 1/4" FNPT	1.85"
AD-638MSS-4MFS	316L SS 1/4 MALE FACE SEAL	2.67"
AD-638MSS-4TS	316L SS 1/4" TUBE STUB	1.78"
AD-638MSS-8TS	316L SS 1/2" TUBE STUB	2.12"

\*Blank plug available with ring & chain on request

## 3 PIECE ADAPTORS (INCLUDES SILVER PLATED 303 SS NUT, 316L SS NIPPLE & SS OUTLET ADAPTOR)

PART NUMBER	DESCRIPTION	L
AD-638F660M-SS	STAINLESS STEEL CGA 638 FEMALE X CGA 660 MALE	3.90"
AD-638F670M-SS	STAINLESS STEEL CGA 638 FEMALE X CGA 670 MALE	3.90"
AD-638FBS6M-SS	STAINLESS STEEL CGA 638 FEMALE X BS 6 MALE	3.75"
AD-638FDIN8M-SS	STAINLESS STEEL CGA 638 FEMALE X DIN 8 MALE	3.77"
AD-638FJIS26RM-SS	STAINLESS STEEL CGA 638 FEMALE X JIS 26R MALE	3.63"



Additional configurations available on request

VALVE, FITTING OR OTHER COMPONENT FUNCTION, PROPER INSTALLATION, MATERIALS COMPATIBILITY, ADEQUATE RATINGS, OPERATION AND MAINTENANCE ARE THE RESPONSIBILTY OF THE SYSTEM DESIGNER AND USER.



PRODUCT FAILURE, IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.



GasFlo Products Inc. CGA Ultra High Integrity Service Cylinder Connections are Manufactured to CGA V-1 Standards
Additional materials and configurations available on request. Minimum order quantities may be required.



@GasFlo Products, Inc. 2016