CGA COMPRESSED GAS SERVICE CYLINDER CONNECTIONS



CONNECTION NO. 660

PRESSURES UP TO 3000 PSI

INLET CONNECTION

RIGHT HAND

FEMALE NUT, NIPPLE & GASKET

Cylinder valve outlet Right hand Male



			CO	NNECTIO	N NO. 660	All dimensions are in inches - for reference only, subject to char
		CY	LINDE	R VALV	E OUTLET CAPS	······································
PART NUMBER	DESCRIPTION				L	- = L" = -
CAP-660BR-P	BRASS W/ POLY DISC LES	S RING &	CHAIN		0.54" DUST CAPS	
CAP-660BR-PR	BRASS W/ POLY DISC				0.54"	1-1/4" HEX
CAP-660BR-TCR	BRASS W/ TEFLON CALCI		DISC		0.54"	(Ø1.25"
CAP-660CH-PR	NICKEL PLATED BRASS W/ POLY DISC				0.54"	
CAP-660SS-PR	303 STAINLESS STEEL W/				0.54"	
CAP-660SS-TCR	303 STAINLESS STEEL W/			FILLED DIS		Contractor Contractor
		TEI EON C				3.75"
					ASKETS	w
PART NUMBER	DESCRIPTION	D	H	W		
GSK-60-T	VIRGIN PTFE	.937	.375	.062		
GSK-60-K	VIRGIN PCTFE	.937	.375	.062		
I	NLETS X 1/4" MALI	E NATI	ONAL	PIPE TH	READ (INCLUDES NUT, N	IPPLE & PTFE GASKET)
PART NUMBER	DESCRIPTION			L	BRASS OR NICKEL PLATED	
INL-660BR-4M-48	BRASS			3.00"	BRASS NUT, NIPPLE &	Ø.176"
INL-CV660BR-4M	BRASS W/ CHECK VALVE			2.625"	GASKET	
INL-660CH-4M-48	NICKEL PLATED BRASS			3.00"		
INL-CV660CH-4M	NICKEL PLATED BRASS W	// CHECK V	ΔIVE	2.625"		
INL-660M0-4M-30F	MONEL			1.875"	MONEL NUT, NIPPLE &	L"
INL-660M0-4M-56	MONEL			3.50"	GASKET	
INL-660SS-4M-30	STAINLESS STEEL			1.875"		φ.176" -
INL-660SS-4M-42	STAINLESS STEEL			2.625"	STAINLESS STEEL	
INL-660SS-4M-56	STAINLESS STEEL			3.50"	303 NUT, 316L NIPPLE &	
INL-660SS-4M-70	STAINLESS STEEL			4.375"	GASKET OPTIONAL INTEGRA	
INL-CV660SS-4M	STAINLESS STEEL W/ CHE	ECK VALVE		2.625"	CHECK VALVE	
	NLETS X 1/4 MALE	FACE	SEAL	(INCLUDI	S 303 SS NUT, 316L SS NI	IPPLE & PCTFE GASKET)
						.73" 1-1/4" HEX
PART NUMBER	DESCRIPTION			L		μ······μ···μ·····φ.180" –]
INL-660SS-4MFS-30	STAINLESS STEEL 12 Ra			1.875"		
INL-660SS-4MFS-P	STAINLESS STEEL 9 Ra E	P		1.875"		
Available with Check Valve upo	n request EP =	Electropolishe	d ID			
INLETS A PART NUMBER	DESCRIPTION	LD 310		LUDES	T	T, 316L SS NIPPLE & PCTFE GASKET)
INL-660SS-4TS-35F	STAINLESS STEEL 12 Ra*			2 .1875"	1/4"OD X .035" WALL	
INL-660SS-4TS-P	STAINLESS STEEL 9 Ra El			2.1875"	1/4"0D X .035" WALL	
	STAINLESS STEEL 9 Na L				1/4"0D X .035" WALL	
INL-CV660SS-4TS	STAINLESS STEEL W/ CH	LON VALVE		2.21"		
INL-660SS-6TS		D		1.875"	3/8"0D X .035" WALL	
	STAINLESS STEEL 9 Ra El	г		1.875"	3/8"0D X .035" WALL	■ L"∎
				1 075%	1/020D V 0402 WALL	
INL-660SS-6TS-P INL-660SS-8TS-30F INL-660SS-8TS-P	STAINLESS STEEL 12 Ra Stainless Steel 9 Ra Ei	2		1.875" 1.875"	1/2"0D X .049" WALL 1/2"0D X .049" WALL	0 Pigtail Handle available EP = Electropolished ID



19 Industrial Road, Fairfield, NJ 07004 Phone: 973-276-9011 Fax: 973-276-9014 www.gasflo.com

CGA660-2018

Member Compressed Gas Association







PRESSURES UP TO 3000 PSI

