

1. DIMENSIONS ARE IN INCHES.
2. VALVE BODY IS ELECTROPOLISHED PRIOR TO ASSEMBLY.
3. WELDS BRUSHED AFTER WELDING.
4. EACH ASSEMBLY IS HELIUM LEAK TESTED WITH 2000 PSI HELIUM AND A MASS SPECTROMETER LEAK DETECTOR.
5. ULTRASONICALLY D.I. CLEANED.
6. SINGLE POLY BAGGED. BAG LABELED WITH GFP LOGO, P/N, "ULTRASONICALLY D.I. CLEANED" AND "MADE IN THE USA".


Technical drawing of a Tee fitting, showing a top view and a side view.

Top View:

- Port size: $(\phi 1.00)$
- Port type: $2 \times 10-32\text{UNF}-2\text{B THREAD}$
- Port angle: $(2 \times 45^\circ)$

Side View:

- Total height: (2.52)
- Height of main body: (1.007)
- Width of main body: (1.125)



SALES DRAWING
UNCONTROLLED
FOR
REFERENCE
ONLY

DESCRIPTION:		
VALVE 1/4 TN.DIA.PACKLESS 1/4 FFSX1/4 FFS SS EP		
PART NUMBER:		
VLV-QSL-44SS-FFSFFS-P		
SIZE: A	SCALE: NTS	MATL: SEE B.O.M.
SHEET NUMBER: 1 OF 1		DRAWN BY: aparadiseasher on 08/04/2015

THIS DOCUMENT CONTAINS INFORMATION THAT IS THE PROPRIETARY AND CONFIDENTIAL PROPERTY OF GASFLO PRODUCTS INC. AND MAY BE USED ONLY FOR AUTHORIZED PURPOSES. THIS DOCUMENT MAY NOT BE REPRODUCED WITHOUT GASFLO PRODUCTS INC. PRIOR WRITTEN CONSENT.



APPR: mbojcik on 02/26/2018