


ITEM	PART NAME	MATERIAL	QTY.
1	BODY	316L SST	1
2	SEAT INSERT	PCTFE	1
3	DIAPHRAGM ASSY	316L SST/COPPER	1
4	BONNET	303 SST	1
5	STEM	416 SST	1
6	HANDLE	BLUE ANODIZED ALUMINUM	1
7	WASHER	18-8 SST	1
8	SCREW	18-8 SST	1
9	DELETED	DELETED	DELETED
10	DELETED	DELETED	DELETED
11	GLAND	316L SCM SST	1
12	NUT	303 SST	1

SPECIFICATIONS:
 PRESSURE RATING: 3500 PSI
 FLOW COEFFICIENT $C_v = .13$
 SEAT ORIFICE SIZE: $.125 \phi$
 SEAT MATERIAL: PCTFE
 TEMPERATURE LIMITS:
 -65° F TO 150° F
 MAX. ALLOWABLE SEAT LEAKAGE:
 2 x 10⁻⁸ ATM CC/SEC He
 MAX. INBOARD LEAKAGE:
 2 x 10⁻⁸ ATM CC/SEC He
 WETTED SURFACES: 316L SST,
 PCTFE.

NOTES:

1. DIMENSIONS ARE IN INCHES.



UNCONTROLLED
 For Reference Only
 FAS 6/11/2014

GasFlo Products Inc.
Fairfield, N.J.

SALES DRAWING- PACKLESS VALVE
 1/4 FFS x 1/4 MFS SS W/ LOTO

DWG: SALES-VLV-SL-44SS-FFSMFS-ALD REV. B

REV	DESCRIPTION	DATE
B	GLAND MATERIAL WAS 303 SST; NUT MATERIAL WAS 316L SCM SST	6/11/2014
A	REDRAWN DELETING ITEMS 9 & 10 FROM B.O.M.; (2.15) WAS (3.02)	4/4/2014

MAT'L: SEE B.O.M.
DWN: MB
SHT: 1 OF 1
SCALE: 1:1
DATE: 11/4/09

THIS DOCUMENT CONTAINS INFORMATION THAT IS THE PROPRIETARY AND CONFIDENTIAL PROPERTY OF GASFLO PRODUCTS INC. AND MAY BE USED ONLY FOR AUTHORIZED PURPOSES. THIS DOCUMENT MAY NOT BE REPRODUCED WITHOUT GASFLO PRODUCTS INC. PRIOR WRITTEN CONSENT